



TSR-OS15

钛白粉

产品描述

TSR-OS15是一种塑料、色母专用金红石型钛白粉。优化配方的无机表面包覆和有机表面处理,使产品在塑料加工体系中的耐温性、加工流动性及耐候性等方面得到出色的体现。该产品可以为高浓度热塑性色母赋予出色的熔体流动性能。

产品用途

塑料、色母专用。

产品标准

项目	指标
TiO ₂ 含量 %	≥ 93
白度 %	≥ 98.2
消色力 雷诺兹数	≥ 1800
吸油量 g/100g	17~22
金红石含量 %	≥ 98
PH 值 %	6.5~8.5
筛余物 (45μm) %	≤ 0.05
挥发份 (105℃) %	—
油分散性 μm	—
电阻率 Ω · m	≥ 80

包装规格

25公斤 / 袋的纸塑阀口袋。

储存条件

应该储存在通风干燥的地方,避免雨水、酸性或者碱性物质接触。

如需样品或更多信息请联系

上海铸友锆钛新材料有限公司

Tel: 86-21-51903686

Fax: 86-21-51903685

Mob: 86-18616780612

Web: www.shzhuyou.com

Email: sales@shzhuyou.com



TSR-OS15

TITANIUM DIOXIDE

PRODUCT DESCRIPTION

TSR-OS15 is a kind of rutile titanium dioxide for plastic and masterbatch exclusive use. With inorganic surface coating and organic surface treatment according to optimized formula, the product exhibits outstanding temperature tolerance, processing fluidity and weather resistance in plastic processing system, and can endow high-concentration thermoplastic masterbatch with outstanding melt flow performance.

MAIN APPLICATION

It can be used in plastic and masterbatch exclusive.

TYPICAL PROPERTIES

Properties	Indicator
TiO ₂ Content %	≥ 93
Brightness %	≥ 98.2
Tinting Strength Reynolds Standard	≥ 1800
Oil Absorption g/100g	17~22
Rutile Content %	≥ 98
PH value	6.5~8.5
Residue(45μm) %	≤ 0.05
Volatile Substance at 105℃ %	—
Dispersibility μm	—
Resistivity Ω · m	≥ 80

PACKING SPECIFICATION

25kg white plastic valve bag.

PRODUCT STORAGE

It should be stored in dry and ventilated place, which should be rain resistant, exposure resistant and no contacts with acid or alkaline.

FOR SAMPLE OR FURTHER INFORMATION CONTACT

Shanghai Zhuyou Zirconium & Titanium New Materials Co.,Ltd

Tel: 86-21-51903686

Fax: 86-21-51903685

Mob: 86-18616780612

Web: www.shzhuyou.com

Email:sales@shzhuyou.com